

#### **FINAL MARINE ADHESIVE**

# SECTION 1: IDENTIFICATIONS OF THE SUBSTANCE /MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product form : ONE PART POLYURETHANE

Trade name : FINAL MARINE

Type of product : ADHESIVE, POLYURETHANE

Product group : TRADE PRODUCT

#### 1.2. Relevant identified uses of the substance or mixture and uses discouraged

Intended for general public.

#### 1.3. Details of the supplier providing the safety data sheet

Head office: Final İthalat İhracat Sanayi Ve Ticaret Limited Şirketi. Halkalı Merkez Mah. Dereboyu Cad.

34303 küçükçekmece/ İstanbul

Phone: +90 (212) 979 08 53

info@final-ticaret.com www.final-ticaret.com

#### 1.4. Emergency telephone number

Poison emergency hotline İstanbul: +90 (212) 979 08 53.

#### **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1. Label elements

#### Signal word

Danger

#### **Symbols**

Exclamation mark | Health Hazard |

#### **Pictograms**





GHS07

GHS08

#### **Hazard Statements**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

# KIMYA SANAYI VE TICARET LIMITED ŞİRKETİ

## **MATERIAL SAFETY DATA SHEETS**

May cause an allergic skin reaction.

Harmful if inhaled.

May damage fertility or the unborn child.

May cause cancer.

#### **Precautionary Statements**

#### General:

Keep out of reach of children.

Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

In case of inadequate ventilation wear respiratory protection.

Wear protective gloves.

Contaminated work clothing must not be allowed out of the workplace.

#### Response:

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

If on skin: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

If exposed or concerned: Get medical advice/attention.

#### Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

#### **Supplemental Information:**

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

#### **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Ingredient	C.A.S. No.	% by Wt
Urethane Polymer	68611-34-7	30 - 60 Trade Secret *
Talc	14807-96-6	15 - 40 Trade Secret *



Titanium Dioxide	13463-67-7	5 - 10 Trade Secret *
Carbitol Acetate	112-15-2	1 - 5 Trade Secret *
Fumed Silica	112945-52-5	0.5 - 5 Trade Secret *
Zinc Oxide	1314-13-2	< 2.5 Trade Secret *
Alkyl Isocyanate Silane	85702-90-5	0.5 - 1.5 Trade Secret *
Heptane	142-82-5	< 1 Trade Secret *
Toluene	108-88-3	< 1 Trade Secret *
Toluene Diisocyanate	26471-62-5	< 1 Trade Secret *
(Gamma-Mercaptopropyl)	4420-74-0	< 0.19 Trade Secret *
trimethoxy silane		
Hexamethylene Diisocyanato	822-06-0	< 0.015 Trade Secret *

#### **SECTION 4: FIRST AID MEASURES**

#### 4.1. Description of first aid measures:

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### **Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest). Allergic skin reaction (redness, swelling, blistering, and itching).

#### **SECTION 5: FIREFIGHTING MEASURES**

#### 5.1. Suitable extinguishing media

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

#### **SECTION 6: HANDLING AND STORAGE**

#### 6.1. Precautions for safe handling

# KIMYA SANAYI VE TICARET LIMITED ŞIRKETİ CHEMICALS I SEALANTS I ADHESIVES

# **MATERIAL SAFETY DATA SHEETS**

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (gloves, respirators, etc.) as required.

#### 6.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Keep cool. Protect from sunlight. Store away from heat. Store away from amines.

#### SECTION 7: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 7.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin, Ototoxic ant
Toluene	108-88-3	OSHA	TWA:200 ppm; CEIL:300 ppm	
SILICA, AMORPHOUS	112945-52- 5	OSHA	TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m3	
Zinc Oxide	1314-13-2	ACGIH	TWA (respirable fraction):2 mg/m3; STEL (respirable fraction):10 mg/m3	
Zinc Oxide	1314-13-2	OSHA	TWA (as total dust):15 mg/m3; TWA (respirable fraction):5 mg/m3; TWA (as fume):5 mg/m3	
Titanium Dioxide	13463-67-7	ACGIH	TWA:10 mg/m3	A4: Not class. as human carcin
Titanium Dioxide	13463-67-7	OSHA	TWA (as total dust):15 mg/m3	
Heptane	142-82-5	ACGIH	TWA:400 ppm; STEL:500 ppm	
Heptane	142-82-5	OSHA	TWA:2000 mg/m3(500 ppm)	



Talc	14807-96-6	ACGIH	TWA (respirable fraction):2 mg/m3	A4: Not class. as human carcin
TALC	14807-96-6	OSHA	TWA - Use asbestos limits:	
Talc	14807-96-6	OSHA	TWA concentration(respirable):0.1 mg/m3(2.4 million of particles/cu. ft.); TWA:20 millions of particles/cu. ft.	
Toluene Diisocyanate	26471-62-5	ACGIH	TWA (inhalable fraction and vapor):0.001 ppm;STEL(inhalable fraction and vapor):0.005 ppm	A3: Confirmed animal carcin., Dermal/Respiratory Sensitizer
Hexamethylene Diisocyanato	822-06-0	ACGIH	TWA:0.005 ppm	

ACGIH: American Conference of Governmental Industrial Hygienists.

AIHA: American Industrial Hygiene Association.

CMRG: Chemical Manufacturer's Recommended Guidelines.

OSHA: United States Department of Labor - Occupational Safety and Health Administration.

TWA: Time-Weighted-Average.

STEL: Short Term Exposure Limit.

CEIL: Ceiling.

#### **SECTION 8: PHYSICAL AND CHEMICAL PROPERTIES**

#### 8.1. Information on basic physical and chemical properties

Physical state Solid

Color Amber Honey

Specific Physical Form Paste

Odor Urethane
Density 1.36 g/ml

Specific Gravity 1.36 [Ref Std: WATER=1]

Viscosity 100,000 - 500,000 centipoise

Hazardous Air Pollutants <=0.2 % weight [Test Method: Calculated]

Percent volatile 2.9 % weight

VOC Less H2O & Exempt Solvents 40 g/l [Test Method: tested per EPA method 24]

#### **SECTION 9: TOXICOLOGICAL INFORMATION**

Inhalation:

# KIMYA SANAYI VE TICARET LIMITED ŞIRKETİ CHEMICAL S. I. SEALANTS. I. ADHESIVES

## **MATERIAL SAFETY DATA SHEETS**

#### Harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

#### **Skin Contact:**

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### **Eye Contact:**

Contact with the eyes during product use is not expected to result in significant irritation.

#### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Ingredient	CAS No.	Class Description	Regulation
Titanium dioxide	13463-67-7	Grp. 2B: Possible	International Agency for
		human carc.	Research on Cancer
Toluene Diisocyanate	26471-62-5	Anticipated human	National Toxicology Program
		carcinogen	Carcinogens
Toluene diisocyanatos	26471-62-5	Grp. 2B: Possible	International Agency for
		human carc.	Research on Cancer

#### **SECTION 10: DISPOSAL CONSIDERATIONS**

#### 10.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

# KIMYA SANAYİ VE TİCARET LİMİTED ŞİRKETİ

## **MATERIAL SAFETY DATA SHEETS**

#### **SECTION 11: ECOLOGICAL INFORMATION**

#### **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

#### **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

#### **SECTION 12: ACCIDENTAL RELEASE**

#### 12.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### 12.2. Environmental precautions

Avoid release to the environment.

#### 12.3. Methods and material for containment and cleaning up

Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations

#### **SECTION 13: TRANSPORT INFORMATION**

Classification for ROAD and Rail transport (ADR/RID):

- 13.1 UN number or ID number Not applicable
- 13.2 UN proper shipping name Not regulated for transport
- 13.3 Transport hazard class(es) Not applicable
- 13.4 Packing group Not applicable
- **13.5 Environmental hazards** Not considered environmentally hazardous based on available data.
- **13.6 Special precautions for user** No data available.



### **SECTION 14: REGULATORY INFORMATION**

#### **EPCRA 311/312 Hazard Classifications:**

#### **Physical Hazards**

Not applicable

Health Hazards	
Acute toxicity	\
Carcinogenicity	
Reproductive toxicity	\
Respiratory or Skin Sensitization	\

# Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	C.A.S. No	<u>% by Wt</u>
Zinc Oxide (ZINC	1314-13-2	Trade Secret < 2.5
COMPOUNDS)		
Carbitol Acetate (GLYCOL	112-15-2	Trade Secret 1 - 5
ETHERS)		
Toluene Diisocyanate	26471-62-5	Trade Secret < 1
Toluene Diisocyanate	26471-62-5	Trade Secret < 1
(Benzene, 1,3-		
diisocyanatomethyl-)		

This material contains a chemical which requires export notification under TSCA Section 12[b]:

Ingredient (Category if applicable)	C.A.S. No	Regulation	Regulation
Toluene Diisocyanate (Benzene,	26471-62-5	Toxic Substances	Proposed
1,3-		Control Act (TSCA) 5	
diisocyanatomethyl-)			



**SNUR or Consent** 

**Order Chemicals** 

Toluene Diisocyanate 26471-62-5 Toxic Substances Proposed

Control Act (TSCA) 5

SNUR or Consent

**Order Chemicals** 

This material contains a chemical subject to a proposed EPA Significant New Use Rule (TSCA Section 5)

Ingredient (Category if applicable) C.A.S. No Reference

Zinc Oxide (ZINC COMPOUNDS) 1314-13-2 Trade Secret < 2.5

#### **SECTION 15: STABILITY AND REACTIVITY**

#### 15.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

#### 15.2. Chemical stability

Stable.

#### 15.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 15.4. Conditions to avoid

Heat

#### 15.5. Incompatible materials

Reaction with water, alcohols, and amines is not hazardous if container can vent to the atmosphere to prevent pressure buildup.

**Amines** 

Alcohols

Water

#### 15.6. Hazardous decomposition products

<u>Substance</u> <u>Condition</u>



None known.

Refer to section hazardous decomposition products during combustion.

#### **SECTION 16: Other information**

#### **NFPA Hazard Classification**

Health: 2 Flammability: 1 Instability: 1 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	16-3092-0	Version Number:	16.04
Issue Date:	11/01/22	Supercedes Date:	05/02/22

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Final MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Final product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Final product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Final product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. Final provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Final makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from Final