

FINAL PVC ELECTRICAL TAPE

SECTION 1: IDENTIFICATIONS OF THE SUBSTANCE /MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product form : ONE COMPONENT
Trade name : FINAL PVC ELECTRICAL TAPE
Type of product : RUBBER ADHESIVE
Product group : TRADE PRODUCT

1.2. Relevant identified uses of the substance or mixture and uses discouraged

Intended for general public.

1.3. Details of the supplier providing the safety data sheet

Head office: Final İthalat İhracat Sanayi Ve Ticaret Limited Şirketi. Halkalı Merkez Mah. Dereboyu Cad.
34303 küçükçekmece/ İstanbul

Phone: +90 (212) 979 08 53

info@final-ticaret.com www.final-ticaret.com

1.4. Emergency telephone number

Poison emergency hotline İstanbul: +90 (212) 979 08 53.

SECTION 2: HAZARDS IDENTIFICATION

Chemical Name	%	CAS No. or Note
Rubber Adhesive	8-18	
PVC resin	52-67	[9002-86-2]
Plasticizers	20-35	[117-81-7]

SECTION 3: PHYSICAL AND CHEMICAL PROPERTIES

Specific Gravity (H₂O=1) :1.25-1.45
Softening Point :>100°C
Decomposition Temperature :260(°C)/500o F
Appearance and Odor :Solid appearance and with slight odor of PVC material

SECTION 4: FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): 320-390C (ASTM D-1929).

Extinguishing Media: water, dry chemical foam, CO2.

Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

Unusual Fire and Explosion Hazards: Any vinyl can be forced to burn by continuous application of intense Heat.

SECTION 5: HANDLING AND STORAGE

Waste Disposal Method

Use approved disposal methods as recommended by state and local agencies.

Precautions to Be Taken in Handling and Storing

Stored in cool, dry, well-ventilated area, away from flammable materials or sources of heat and flame.